

## TRUCK CHASSIS SPECIFICATIONS

### CAB AND CHASSIS SPECIFICATIONS

New, 2016 or 2017 Model Truck

Diesel Cummins; Engine, *minimum* of 250 HP and 620lb.-ft. Torque

Allison Automatic Transmission, RDS Series, 3000 or 3500 series

Minimum of 35,000 lbs. GVWR

Wheelbase- As required for optimum weight distributions of body-Refer to body dealer for requirements

Front Axle-12,000 lbs.

Front Suspension-12,000 lbs.

Rear Suspension – Minimum 26,000 lbs. – Prefer 31,000 lbs.

Tires- 11R22.5 Front and Rear

Wheels-Painted Steel Disc.

Auxiliary or Helper Springs – Min. 4000 lbs.

Power Steering

Air Brakes w/ABS, Air Dryers and Automatic Slack Adjusters

13 CFM Compressor Minimum

West Coast Style Mirrors, and Convex Mirrors- Both Sides

Minimum 50 gallon Fuel Tank

Air Conditioning w/ Heat

AM/FM Radio

Cruise Control

Fuel/ Water Separator

Paint White to match cab

Body Builders Wiring Harness

Front Tow Hooks-Frame Mounted

12V Cigarette Lighter- Power Plug

Min. 110 V Alternator

Battery Disconnect Switch

Operators, Parts and Service Manual

Please include the following information regarding the equipment being proposed:

Truck Lead Time-Time to build and ship to body mounting facility 120-180 days

Warranty Terms

Truck Services Facility-Closest full service facility which will perform warranty work: 46 miles from Hamlet

## TRUCK-CAB AND CHASSIS SPECIFICATIONS

	YES	NO	OFFERED
2016			
2017 Model Year	_____	_____	_____
35,000 #GVWR	_____	_____	_____
168" Clear CA	_____	_____	_____
120,000 PSI Frame Rails	_____	_____	_____
Front Tow Hooks	_____	_____	_____
6.7l, 280 HP ISB Diesel Engine (Cummins)	_____	_____	_____
660 FT.-LBS Torque	_____	_____	_____
130A Alternator	_____	_____	_____
Fuel-Water Separator	_____	_____	_____
Horizontal or Vertical Exhaust	_____	_____	_____
-No exhaust components (DPF, etc.) under right side of cab			
Allison 3500RDS 6-Speed Automatic	_____	_____	_____
Auto Neutral System Required	_____	_____	_____
1,250 CCA Batteries	_____	_____	_____
Jump Start Stud	_____	_____	_____
12,000 # Front Axle	_____	_____	_____
12,000 # Front Suspension	_____	_____	_____
Front Shock Absorbers	_____	_____	_____
23,000 # Rear Axle	_____	_____	_____
31,000 # Rear Suspension	_____	_____	_____
4,500 # Rear Overloads	_____	_____	_____
6.17 Rear Axle Ratio	_____	_____	_____
ABS Air Brakes	_____	_____	_____
LH Fuel Tank (45 Gal.)-No Exceptions	_____	_____	_____
Chrome Headlight Bezel	_____	_____	_____
Chrome Grille	_____	_____	_____
Chrome Front Bumper	_____	_____	_____

	YES	NO	OFFERED
Fender-Mounted Front Turn Signals	_____	_____	_____
Air Horn	_____	_____	_____
Upgraded Interior Trim Level / Gauge Pkg.	_____	_____	_____
Air Conditioning, Heater, Defrost	_____	_____	_____
Air Driver's Seat	_____	_____	_____
Passenger Seat	_____	_____	_____
AM /FM/CD/CLOCK	_____	_____	_____
Tilt Steering	_____	_____	_____
Cruise Control	_____	_____	_____
Power Windows	_____	_____	_____
Power Door Locks	_____	_____	_____
Heated Mirrors w/ Lighted Heads	_____	_____	_____
8" Convex Mirrors	_____	_____	_____
11R22.5 Front Tires (Steer Tread)	_____	_____	_____
11R22.5 Rear Tires (Traction Tread)	_____	_____	_____
Hub-Piloted Steel Disc Wheels	_____	_____	_____
White Exterior Paint	_____	_____	_____
Gray Interior (HD Vinyl)	_____	_____	_____
24 Mo / Unlimited Miles Basis Warranty	_____	_____	_____
36 Mo / Unlimited Miles Corrosion Warranty	_____	_____	_____
24 Mo / Unlimited Miles Roadside Assistance	_____	_____	_____
24 Mo / Unlimited Miles Engine Warranty	_____	_____	_____
24 Mo / Unlimited Miles Transmission Warranty	_____	_____	_____
Low Air Pressure Warning Light and Audible Alarm	_____	_____	_____